

Following preloads are allowed before loading Lupranate T 80 ex Korea, Lupranate T 80 Type 1 Isocyanate, Lupranat T 80 M, Lupranate® T80 TYPE 1 BMBcert™ M1 I Isocyanate, Lupranat T 80 B, Lupranat T 80 B TR, Lupranat T 80 BM, Lupranate T 80 ex China.

Tank containers, that are to be loaded with TDI, may only be loaded with one of the products on this list, before they are loaded with TDI again or must have been purged with nitrogen after cleaning, until a dew point of at least -20°C is reached.

This proof of dew point must not be older than three days in order to exclude the ingress of moisture.

Product Name
Lupranat® T 80 M
Lupranate T 80 Type 1 ISO
Lupranate T 80 ex China
Lupranate® T 80 ex Korea
Lupranat T 80 B
Lupranat T 80 B TR
Lupranat® T 80 BM
Desmodur® T 80
Desmodur® T 80 NP
Desmodur® T 100
Desmodur® T 100 SP
Desmodur® T65N
Ongronat® 1080
Ongronat® 1100
Ongronat® 1065
VORANATE* T80.20
Voranate T-80 Type 1 TDI
Caradate 80
TDI 80/20-0201
TDI 100 (100% 2,4-TDI)
Lupranate®T80TYPE 1 BMBcert™ M1 Isocyanate
WANNATE TDI-80
SABIC TDI 0380