

Alcohols, Glycol Ethers & Acetates from BASF

Your reliable partner to shape a sustainable future.

Product Name	CAS-Number	Chemical name [Formula]	Paints & Coatings	Pharmaceuticals ¹⁾	Detergents	Lubricants	Textile & Leather Chemicals	Crop Protection	As an Intermediate Chemical	Molar mass g/mol	Boiling range (1013 mbar) [DIN 53171] °C	Density 20°C [DIN 51757] g/cm ³	Refractive index n _D 20 [DIN 51423]	Viscosity 20 °C [DIN 51562] mPa·s	Evaporation number [DIN 53170]; Ether = 1	Flash point [DIN EN ISO 2719] °C	Ignition temperature [DIN 51759] °C	Temperature Class [DIN EN 60079-14] (VDE 0465)	Explosion limit Vol. %
Alcohols																			
n-Butanol	71-36-3	n-Butyl alcohol [C ₄ H ₁₀ O]	x					x		74.12	116 - 118	0.809 - 0.811	1.398 - 1.400	2.9	33	35	325	T2	1.7 - 11.2
2-Ethylhexanol	104-76-7	2-Ethylhexan-1-ol, 2-Ethyl-1-hexanol, Isooctanol [C ₈ H ₁₈ O]	x	x	x		x	x		130.23	186	0.832	1.431-1432	9.8454					
Isobutanol	78-83-1	i-Butanol, Isobutyl alcohol, 2-Methyl-1-propanol [C ₄ H ₁₀ O]	x					x		74.12	106 - 108	0.801 - 0.803	1.395 - 1.396	3.95	25	27	430	T2	1.7 - 11
C13-C15 Alcohol	85566-16-1	C13-C15 Alcohols, linear and branched [C ₁₃ H ₂₇ OH - C ₁₅ H ₃₁ OH]	x	x						200.37 - 228.41	265 - 292	0.82 - 0.84	-	11.9	-	142	240	T3	0.8
Isotridecanol N	27458-92-0	Mixture of primary tridecyl alcohol isomers [C ₁₃ H ₂₇ OH]	x	x	x			x		200.36	251 - 263	0.8436	1.4480 - 1.4485	36.2	> 10 000	115	260	T3	0.6
Pentanol Mixture	71-41-0 137-32-6 123-51-3	Pentanol, branched and linear [CH ₃ (CH ₂) ₄ OH CH ₃ CH ₂ CH(CH ₃)CH ₂ OH]			x			x	x	88.2	128 - 137	0.815	1.41	4.3	65	45	320	T2	1.2 - 10
n-Pentanol	71-41-0	n-Pentanol [CH ₃ (CH ₂) ₄ OH]	x	x		x		x	x	88.2	137 - 139	0.815	1.41	3.3	96	49	300	T3	1.6 - 8.0
n-Propanol	71-23-8	n-Propyl alcohol [CH ₃ (CH ₂) ₂ OH]	x	x	x			x		60.1	96.5 - 98	0.804	1.385	2.3	16	24	395	T2	2.4 - 13.2
Propylheptanol	10042-59-8	2-Propylheptane-1-ol, 2-Propyl-1-heptanol [C ₁₀ H ₂₂ OH]	x		x	x			x	158.28	207 - 212	0.8322	1.4371	15.2	-	100	265	T3	-
3-Methyl-1-Butanol	123-51-3	3-Methylbutanol [CH ₃ C(CH ₃)HCH ₂ CH ₂ OH]	x	x		x		x	x	88.2	129 - 130	0.828	-	-	-	43.5	335	T2	1.0 - 8.2
Aldehydes																			
n-Butyraldehyde	123-72-8	Butyraldehyde, Butanal [C ₄ H ₈ O]		x				x	x	72.11	75 - 76	0.800	1.381	0.45	-	-12	195	T4	1.7 - 12.5
Isobutyraldehyde	78-84-2	i-Butyraldehyde, 2-Methylpropanal [C ₄ H ₈ O]		x				x	x	72.1	63 - 65.4	0.788	1.3709	0.5377	-	-24	180	T4	1.6 - 11
Propionaldehyde	123-38-6	n-Propanal, Propionaldehyde [CH ₃ CH ₂ CHO]		x			x	x	x	58.1	47 - 48	0.797	-	0.375	-	-40	175	T4	2.3 - 21

Product Name	CAS-Number	Chemical name [Formula]								Boiling range [1013 mbar] [DIN 53171] °C	Density 20 °C [DIN 51757] g/cm ³	Refractive index n _D 20 [DIN 51423]	Viscosity 20 °C [DIN 51563] mPa·s	Evaporation number [DIN 53170] Ether = 1	Flash point [DIN EN ISO 2719] °C	Ignition temperature [DIN 51794] °C	Temperature class [DIN EN 60079-14] [VDE 0165]	Explosion limit Vol. %
			Paints & Coatings	Pharmaceuticals	Detergents	Lubricants	Textile & Leather Chemicals	Crop Protection Chemical	As an Intermediate									
Acetates																		
n-Butyl Acetate	123-86-4	Acetic acid n-butyl ester [CH ₃ COO(CH ₂) ₃ CH ₃]	x	x	x			x	116.2	124 - 128	0.881	1.394	0.7	12	27	415	T2	1.4 - 9.6
Pentyl Acetate	628-63-7*) 624-41-9 123-92-2	Mixture of isomeric pentyl esters of acetic acid, reaction mass of 2-methylbutyl acetate and pentyl acetate [C ₇ H ₁₄ O ₂]	x	x	x			x	130.2	146 - 149	0.876	1.403	0.9	28	40	345	T2	1.4 - 8.4
2-Ethylhexyl Acetate	103-09-3	Acetic acid 2-ethylhexyl ester [CH ₃ COOCH ₂ CH(C ₂ H ₅)(CH ₂) ₃ CH ₃]	x		x				172.3	192 - 205	0.873	1.42	1.6	320	77	270	T3	1.1 - 7.5
Glycol Ethers																		
Butylglycol	111-76-2	2-Butoxyethanol [CH ₃ (CH ₂) ₃ OCH ₂ CH ₂ OH]	x		x	x	x	x	118.2	168 - 172	0.901	1.419	3.3	160	67	230	T3	1.1 - 10.6
Butyldiglycol	112-34-5	2-(2-Butoxyethoxy)-ethanol [CH ₃ (CH ₂) ₃ (OCH ₂ CH ₂) ₂ OH]	x		x	x	x	x	162.2	228 - 232	0.954	1.432	5.9	ca. 3500	105	210	T3	0.7 - 5.9
Butyltriglycol	143-22-6*) 1559-34-8	Mixture of ethylene glycol monoalkyl ethers [CH ₃ (CH ₂) ₃ (OCH ₂ CH ₂) _n OH] [CH ₃ (CH ₂) ₃ (OCH ₂ CH ₂) ₂ OH]	x		x	x	x	x	-	265 - 350	0.994	1.44	10.5	ca. 8000	144	203	T3	0.8 - 3.8
n-Hexylglycol	112-25-4	2-Hexoxy-1-ethanol [C ₈ H ₁₈ O ₂]	x		x				146.2	200 - 212	0.887	1.429	5.3	ca. 1200	94	220	T3	1.2 - 8.4
n-Hexyldiglycol	112-59-4	Diethylene glycol mono hexyl ether, 2-(2-hexyloxy-ethoxy)-ethanol [C ₁₀ H ₂₂ O ₃]	x		x				190.28	262	0.93	-	8.6	-	-	-	-	-
Solvenon® PM	107-98-2	1-Methoxypropanol-2 [CH ₃ CH(OH)CH ₂ OCH ₃]	x		x	x	x	x	90.1	119 - 122	0.92	1.403	1.9	22	32	270	T3	1.7 - 11.5
Solvenon® DPM	34590-94-8	Methoxypropoxypropanol (mixture of isomers) [C ₇ H ₁₆ O ₃]	x		x		x	x	148.2	185 - 195	0.957	1.422	4.1	ca. 380	80	205	T3	1.4 - 10.4
Solvenon® PnB	5131-66-8	1-Butoxy-2-propanol [CH ₃ (CH ₂) ₃ OCH ₂ CH(CH ₃)OH]	x		x				132.2	ca. 170	0.88	1.418	-	125	60	250	T3	1.3 - 9.0
Solvenon® DPnB	29911-28-2	Butoxy dipropanols (mixture of isomers) [C ₁₀ H ₂₂ O ₃]	x		x				190.3	225 - 235	ca. 0.91	1.427	4.4	ca. 1400	101	195	T4	1.0 - 6.2
Solvenon® TPnB	55934-93-5	Mixture of propylene glycol mono butyl ethers [C ₁₃ H ₂₈ O ₂]	x		x				248.4	272 - 282	ca. 0.93	1.432	-	>10 000	129	190	T4	-
Glycol Ether Acetates																		
Butylglycol Acetate	112-07-2	2-Butoxyethyl acetate [CH ₃ (CH ₂) ₃ OCH ₂ CH ₂ OCOCH ₃]	x		x		x		160.2	185 - 188	0.94	1.414	1.8	190	76	300	T3	1.0 - 6.1
Butyldiglycol Acetate	124-17-4	2-(2-Butoxyethoxy) ethyl acetate [CH ₃ (CH ₂) ₃ (OCH ₂ CH ₂) ₂ OCOCH ₃]	x		x		x	x	204.3	238 - 248	0.976	1.426	3.5	> 4 000	102	265	T3	1.0 - 5.3
Methoxypropyl Acetate	108-65-6	1-Methoxy-2-propyl acetate [CH ₃ OCH ₂ CH(CH ₃)OCOCH ₃]	x		x		x		132.2	145 - 147	0.967	1.402	1.2	33	45	315	T2	1.5 - 10.8



We create chemistry

¹⁰ Our products are manufactured according to ISO 9001 and were designed for the use in further chemical syntheses or industrial applications. The quality of the products at the time of passing of risk is determined by BASF's product specification. From our side, the products are not intended to be used for sensitive applications (e. g. cosmetics, personal care, toys, food contact). Therefore, we have not evaluated whether the existing safety data support the use in these applications. It is solely the responsibility of the customer to ensure that any proprietary rights and legislation are observed and required risk assessments are carried out. In particular, the customer is not relieved from carrying out its own investigations and making tests to determine and verify the suitability of the products for a particular purpose prior to use. This includes all required risk assessments and according to measures concerning the use of the products in the intended applications.

WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED GRATIS, IN GOOD FAITH AND BELIEVED TO BE ACCURATE, THEY ARE PROVIDED FOR GUIDANCE ONLY AND BASF ASSUMES NO OBLIGATION OR LIABILITY FOR ANY RESULTS OBTAINED. ALL SUCH BEING GIVEN AND ACCEPTED AT THE READER'S RISK. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE OF OUR PRODUCTS, THE READER IS NOT RELIEVED FROM CARRYING OUT ITS OWN INVESTIGATIONS AND MAKING TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR A PARTICULAR PURPOSE PRIOR TO USE. **NEITHER WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, NOR ANY GUARANTEES ARE MADE/GRANTED REGARDING PRODUCTS DESCRIBED, OR THEIR PROPERTIES, DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESCRIPTIONS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS.** IN NO CASE SHALL THE DESCRIPTIONS, DESIGNS, DATA OR INFORMATION PROVIDED BE CONSIDERED A PART OF ANY SUPPLY AGREEMENT, UNLESS THE PARTIES EXPRESSLY AGREE OTHERWISE.

Version dated 05/2024